

## **COMPACTION MEANS BOMAG.**

If you work your sites hard, you need machines you can rely on. That's why at BOMAG we have specialised in easy handling, robust and safe equipment for decades. And this will never change.

#### HITTING IT BIG WITH SMALL MACHINES.

When BOMAG built the BW 60, the world's first hand-guided double vibratory all-drum drive roller in 1957, the model became a milestone in compaction performance.

The close relationship with our customers back then allowed us, as it still does, to develop machines and systems that make site-work easier. This legacy is something customers around the world value and is the reason the industry places its trust in BOMAG.



## **TABLE CONTENTS.**

06		IPERS
w	IAIV	IFENƏ

- 14 SINGLE DIRECTION VIBRATORY PLATES
- 20 **REVERSIBLE VIBRATORY PLATES**
- 28 HAND-GUIDED VIBRATORY ROLLERS
- 34 MULTI-PURPOSE COMPACTORS
- 42 **BOMAG GENUINE PARTS AND SERVICE**
- 44 PRACTICAL TIPS FOR EARTHWORKS AND ASPHALT
- 46 **PRACTICAL TIPS FOR PAVING WORK**
- 48 **MODEL OVERVIEW**





## **FOUR STROKE WINNER.**

Robust, reliable and extremely tough: these 4-stroke engine BOMAG tampers are ideal for trench and sewage systems, gardening and landscaping, compaction on backfill, foundations, patching and repairs. Less effort to operate, durable, designed to deliver high performance.



## LIGHT WEIGHT MODEL: BT 60 CONVENIENT HANDLING AND LESS DOCUMENTATION EFFORT.

The lightest tamper in this performance class: ideal for long working shifts in confined spaces. The BT 60 also has the lowest hand-arm vibrations:  $< 5 \text{ m/s}^2$  in the standard version. The reference class for professional users.



## BASIC MODELS: BVT 65 FOR ALL-ROUND COMPACTION PERFORMANCE.

Sets the standards in the premium class: for economic use on a wide range of applications. BOMAG performance: outstanding design.



#### DIESEL POWER: MODEL BT 80 D FOR THE MOST CHALLENGING CONDITIONS.

Diesel power for extended use on tough sites. The specialist model for demanding jobs needing extra impact forces and productivity.



## **ROBUST IN THE DETAILS.**

#### LONGER SERVICE LIFE

The two self-cleaning, paper air filter systems allow the petrol-operated machines of the BT series to achieve maximum availability and extended service life.

#### **WELL-LUBRICATED**

A unique BOMAG lubrication system provides optimum oil supply in the crankcase at all angles. The engine is also protected by the automatic oil level check system.



#### **QUICK TO MOVE**

Optional transport wheels for easy handling around site.



#### **ALL AT A GLANCE**

Operating hour counter, tachometer and resettable service display, daily hour counters provide a clear overview.

#### SAFE OPERATION

The height adjustable, anti-vibration guide handle can be adjusted to suit every operator. Ensuring fatigue-free work.




#### **EVERYTHING UNDER CONTROL**

ON/OFF safety easy-action switch for prompt engine and fuel start-up and shutdown.

#### **FULLY PROTECTED**

The engine protection cover provides optimum damage protection on-site.

Even heavy-handling off the delivery truck won't damage the durable plastic, reducing repair costs by up to 33%.




## **NOT JUST CLEAN, BUT PRISTINE.**

Some jobs present bigger challenges than others: e.g. enclosed spaces or deep trenches. The first gas-operated tamper worldwide from BOMAG meets the highest health and safety demands for extreme site conditions.

#### **BREATHE EASILY:**


BOMAG offers the first worldwide models driven by gas, the BT 60 G and BT 65 G tampers. These units excel with almost untraceable CO emissions. They are highly environmentally-friendly and safeguard operator health under extreme job conditions.

These tampers are equipped with the latest 4-stroke engines fuelled by standard propane gas. The two safety bottles can be filled and re-filled with ease on site. A full tank will give 2 hours' operation.





Technical modification may be required in certain markets.





## **QUALITY COMPACTION.**

BOMAG single direction vibratory plates are designed for use on all earthworks, asphalt and paving applications. The range offers the right solution every time plus extra BOMAG reliability and compaction power.

#### LIGHTER WEIGHT MODELS: MODELS BP 10/35 AND BP 12/40.

For a fast repair, small area or patching job. These units offer easy handling and economic operation. Especially useful in tight corners or on areas difficult to access.



#### THE ASPHALT SPECIALIST: MODELS BP 12/50 A AND BVP 12/50 A.

Fitted with a special base plate, this unit is ideal for all asphalt applications. No scuffs on the asphalt surface when turning. This model gives a perfect surface finish.



#### POWER-PACKED UNITS: MODELS BP 20/50, BP 20/50 D, BP 25/50 AND BP 25/50 D.

These are the right plates for the specialist user who needs to meet the highest compaction demands every time.





## THE GREATNESS IS IN THE DETAILS.

#### **OPTIMALLY CUSHIONED**

The hinged guide handle is mounted on large 'silentblock' rubber mounts. This reduces hand-arm vibrations to less than 5 m/s² on both the HP and BVP series. In addition, optional comfort handles are available with hand-arm vibrations  $\leq 2.5$  m/s². This makes things easier for the operator and reduces the documentation effort.



#### **BUILT TOUGH**

For fough-going: the protective frame is designed to protect the engine and other components from impacts, mishaps and rough handling.

#### **QUICKLY FILLED**

The removable water tank on the BP series has a larger capacity and is even equipped with a level indicator.

### MADE SAFE

The V-belt guard, standard on all models, provides the operator with permanent protection from injury and the fully enclosed design results in fewer repairs.







### **MACHINES FOR PROFESSIONALS.**

Reversible vibratory plates are popular choices on many small and medium-sized construction sites. BOMAG offers a full range of models with operating weights from 120 to 750 kg. These are uncompromising compaction units for earthworks, asphalt and block paving.

#### MEDIUM-WEIGHT POWERHOUSES: BPR-PERFORMANCE CLASS 45 TO 60 KN.

The 350 to 500 kg operating weights of these diesel-operated vibratory plates from BOMAG provide excellent compaction results and superb surface coverage, especially on earthworks and paving work.



#### HEAVYWEIGHT POWER PACK: BPR PERFORMANCE CLASS 70 TO 100 KN.

With large working widths and massive compaction power, these heavyweight models provide top performance on tough sites.



#### REMOTE CONTROLLED POWERHOUSE: MODEL BPH 80/65 S.

The ultimate compaction power for trench, sewer and pipeline construction. Radio/cable or cable remote control makes work easy and provides an extra level of safety.



## THOROUGHLY THOUGHT OUT.



Robust, solid rubber transport wheels are quick-mounting, allowing easy movement to the next site. Available on all models up to 300 kg.

#### **GENTLE AND POWERFULL**

The city modul allows to adept the frequency and centrifugal forces to the application available with machines > 500 kg (not for US-variant).



#### **EASILY MANOEUVRED**

The TipControl and integrated reversing protection as standard provide maximum safety and easy operation in the over 500 kg class.


Alternatively, a comfort control lever with low hand-arm vibration values is also available.





#### INDIVIDUALLY ADAPTED

Every operator can select the ideal working position with the height adjustable, low-vibration steering rod.



## **ECONOMIZER. COMPACTION CONTROL.**

The BOMAG ECONOMIZER shows the operator real-time compaction progress on a continuous easy-read display. This support system prevents unnecessary passes

and immediately identifies weak spots. The BOMAG ECONOMIZER is available on all reversible vibratory plates over 350 kg.

### **STONEGUARD - NOTHING GETS BROKEN HERE.**

#### THE PAVING PLATE.

With conventional compaction equipment, the breakage rate of paving stones is often as high as 30%. Costs can easily escalate. The new BOMAG paving plate is designed to prevent this type of loss. The STONEGUARD series includes several models of reversible vibratory plates with operating weights between 150 and 500 kg. Using this unique paving plate, contractors achieve hitherto unachievable results in terms of sur-

face coverage, handling and quality, with the added bonus of reduced block breakage rates.

#### **BENEFITS:**

- Increases working speed by up to 30%
- Prevents edge and paving block breakages
- Allows vibratory compaction to the final block
- Allows vibratory compaction of large slabs
- Prevents damage to surrounding structures



# **COMPACTION QUALITY. EVERY TIME. EVERY SITE.**

#### THE ORIGINAL - BOMAG HAND-GUIDED ROLLERS.

BOMAG has been the leader in handguided rollers since 1957. Beginning with one model, now an entire range of singledrum and double vibratory rollers that have one thing in common: a better compaction result.





#### HEAVY-DUTY DOUBLE VIBRATORY ROLLER: MODEL BW 75 H.

This high-performance wonder is ideal for asphalt construction and earthworks. The 750 mm drum width and the high compaction power of all hand-guided models automatically provides outstanding surface coverage.



## LIGHT DUTY SINGLE DRUM VIBRATORY ROLLER: BW 55 E.

This light all-round model stands out with easy handling in confined spaces. Ideal whenever manoeuvrability and easy transport are key factors. The pioneer in its class.



## HEAVY DUTY SINGLE DRUM VIBRATORY ROLLER: BW 71 E-2.

The BW 71 E-2 excels for surface quality and coverage, especially on asphalt applications and repair and maintenance work. The large 600 mm drum diameter and 710 mm working width give excellent finishing results.



# MILESTONES IN COMPACTION TECHNOLOGY.

No other manufacturer has as many years of experience as BOMAG, as this is where it all began with the first hand-guided double vibratory roller. Technology has developed steadily since then. But one thing remains the same: the unrivalled compaction quality and reliability of a BOMAG roller.



## THE INNER VALUES ARE WHAT REALLY COUNT.

#### **QUICKLY STOWED**

The hinged steering rod offers space-saving transportation and convenient loading.



#### UNIVERSALLY EMPLOYED

 All hand-guided vibratory rollers are equipped with a water tank as standard.

#### **DEPENDABLY POWERED**

The maintenance-free, mechanical drive ensures constant traction on any job.

#### SAFELY OPERATED

From speed control to vibration mode: all functions are easy and safe for the operator to control on one handle.

#### **EASILY STARTED**

Manual or electric start comes as standard with these double vibratory rollers.



#### **BURSTING WITH POWER**

The proven BOMAG double vibration system produces uniquely quiet and smooth running characteristics giving uniform surface quality. Compaction and surface coverage is outstanding with high centrifugal forces and excellent working speed.







# **EARTHWORKS EVOLUTION.**

The BOMAG BMP 8500 articulated, multi-purpose compactor was specially designed for earthworks; it is particularly suitable for compaction on cohesive soils in trenches, backfills, sewer and pipeline construction, and sub-structural and foundation work. And anywhere space gets tight or the job gets hazardous.

# REMOVABLE DRUM EXTENSION WITH PAD FEET.

The working width can be easily varied between 610 and 850 mm with the drum extensions which come as standard. They are ready for use in any trench in minutes.



# ALSO AVAILABLE WITH SMOOTH DRUMS.

The BOMAG BMP 8500 can also be optionally equipped with a smooth drum for improved surface quality without pad footprints, even on sandy materials.



# SUPERIOR TECHNOLOGY.

### MOST RELIABLE ENGINE

Both the modern KUBOTA engine and BOMAG ECOMODE provide the lowest operating costs. If the remate control is not activated, the engine will automatically change to idle speed after a few seconds. That saves hard cash.



Reliability from experience: the original BOMAG drum extender allows you to adapt the working width from 610 to 850 mm in just minutes.

### RELIABLE RADIO CONTROL

With radio/cable remote control, problems caused by intense sunlight, shoring work, or the simultaneous use of other machines are eliminated. Frequency adjustments and malfunctions due to mechanical wear no longer apply.







### SAFE RESPONSE

If the operator enters into the close vicinity of the machine, the travel system is automatically stopped by BOSS (BOMAC Operator Safety System) to prevent accidents.

Nothing could be safer.



### **BUILT-IN SAFETY**

The fully encased exciter housing prevents water and dirt ingress, as well as abrasion to the hydraulic hoses. This increases operational safety and prevents costly repair work over the long term.

Technical modifications may be required depending on the country of distribution.

# ECONOMIZER — KNOWING WHEN THE JOB IS DONE.

The BMP 8500 remote-controlled multi-purpose compactor is best used when conditions become confined or inaccessible. Featuring legendary BOMAG quality, this is the first machine of this type to display compaction progress. Guessing is now a thing of the past.


# THE OPERATOR KNOWS WHEN COMPACTION IS FINISHED.

Unique in compaction technology: The BOMAG ECONOMIZER is integrated into the hood of the BMP 8500, which means it is easy to see and well protected. The unit aids the operator in achieving optimum compaction results and could not be simpler, as there is no need for activation and calibration.

The ECONOMIZER automatically determines compaction progress. This allows the operator to identify weak spots in the subsoil continuously and accurately, and to respond appropriately in good time. Expensive reworking is no longer necessary. In addition, unnecessary passes and overcompaction are also avoided which results in time savings of up to 25%.







# ALWAYS THE RIGHT CHOICE: BOMAG GENUINE PARTS AND SERVICE.

You deliberately opted for a BOMAG when deciding on your machine. To ensure the long-term performance of your equipment, you can also rely on the tried and trusted quality of BOMAG's service and genuine parts.



#### **GUARANTEED BOMAG QUALITY.**

If you work a site hard, you need to be able to rely on your machines. This is why every BOMAG machine is tested thoroughly, inside and out. We have total confidence in the quality of our machines, which is why we offer the 3-2-1 warranty as standard.



#### **ALL SERVICE PARTS IN ONE BOX.**

BOMAG Service Kits are individually compiled by our service experts for your BOMAG machine and contain all the parts required for professional maintenance in one handy package. This not only saves you time, but money - up to 15% compared to individual orders.



#### **UNIQUELY BOMAG.**

BOMAG genuine parts are matched exactly to your machine, and offer reliability and proven quality. Unlike copies, they meet our highest quality standards in terms of functionality and service life so that your BOMAG remains a BOMAG.



#### ALWAYS RELIABLE.

The best service and high availability of genuine parts are included when you purchase your BOMAG. With twelve foreign subsidiaries and over 500 dealers in more than 120 countries, you can count on us as a reliable partner worldwide. No matter where your machine is in operation, we will never let you down!

# **APPLICATION TIPS FOR EARTHWORKS AND ASPHALT.**


Guidelines\* for the non-compacted/compacted layer thickness dependant on soil type and type of compaction equipment.

,ms.x. c	4 - 6 ×  4 - 6 ×  5	kN	kg	Rock
	BT 60	≤15	< 62	-
	BT 65	16-17	62-85	-
	B(V)P 10/xx - BVP 18/45 BP 20/50 (D) BP 25/50 (D)	<20 ≥20 ≥25	47-91 95-109 108-122	-
♦ BOMAG	BPR 25/xx	≤25	≤150	-
	BPR 35/xx	≤35	≤230	-
	BPR 45/55 D, BPR 50/55 D	≤50	≤400	-
	BPR 55/65 D, BPR 60/65 D	≤60	≤460	-
	BPR 70/70 D	≤70	≤600	35 → 40
	BPR 100/80 D, BPH 80/65 S	≤100	>700	50 → 45
	BW 55 E	10	≤170	-
	BW 71 E-2	16	≤530	-
	BW 65 H	22	≤800	-
	BW 75 H	40	≤1100	-
	BMP 8500	72	≤1500	_
	经公司 美工作		SELECTION OF THE PERSON OF THE	

	E.		kN	kg	2 - 4 cm
23475 X 244	V	ET 60, BT 65	14-17	55-85	-
	19	<b>L</b> (V)P 10/35 - BP 20/50 <b>E</b> P 25/50 - BP 25/50 D	10-20 <25	47-109 >108	√. √
		EPR 25/XX EPR 35/XX EPR 45/55 D - BPR 70/70 D	≤25 ≤35 45-70	<150 <300 390-600	✓. - -
	- TA	<b>L</b> W 55 E EW 71 E−2	10-16 10-16	150-500 150-500	√. √
		EW 65 H, BW 75 H	22-40	650-1100	✓


<sup>\*</sup>These guidelines are the result of trial compaction and site operations. Compaction specifications can generally be achieved in four to eight passes under normal application conditions.





# **APPLICATION TIPS FOR PAVING WORK.**

Guidelines\* for the non-compacted/compacted layer thickness depending on soil type and compaction equipment.



<sup>\*</sup>These guidelines are the result of trial compaction and site operations. Compaction specifications can generally be achieved in four to eight passes under normal application conditions.

■ The guide values come from trial compaction and one-site operations.

The specified compaction can be achieved in four to eight passes, under normal application conditions.

			I ST B	> B	S B L/B ≤	80 cm
	MV.	kg	6 cm	8 cm	10 cm	> 10 cm
BPR 25/50	≤25	s150	4	J	-	7.
6/18 35/60 6PR 35/60 D	<b>≤3</b> b	≤23C	1	1	¥	<u>2</u> 8
BPR 50/85 D BPR 50/85 D BPR 60/85 D	≲90	<46C	(#);	2.	,	,

- unsuitable

✓ suitable

- Please observe the laying instructions of the paving stone manufacturer.
   BOMAG GmbH recommends creating trial areas because the different concrete blocks cannot be generalised.

# THE RIGHT MACHINE FOR EVERY JOB.

#### **TAMPER**



Centinugar force. 13 kN Working width: 230 mm



Cenunuyar ibrce. 17kiV Working width: 280 mm



Working width: 280 mm available in EU + CH + NA



Cenunbyar Orce. 17,5 NN Working width: 330 mm not available in US + CN + IN



centinuyar ibrce. r5kn Working width: 230 mm available in DE



Centrityar orce. 17 No Working width: 280 mm available in DE



Centrifugal force: 10 kN Working width: 300 mm



BVP 12/50 A

(N Centrifugal force: 10 kN

m Working width: 300 mm



BMF 18:45 Centrifugal force: 18 kN Working width: 450 mm



Centrifugal force: 18 kN Working width: 450 mm



Centrifugal force: 18 kN Working width: 450 mm available in CN



Centritugal force: 35 KN Working width: 600 mm



Centritugal force: 35 KN Working width: 600 mm



Centritugal force: 40 kN Working width: 600 mm



Centrifugal force: 45 KN Working width: 550 mm



OPR 50 55 D Centritugal force: 50 KN Working width: 550 mm

#### **STONEGUARD**



Available for BPR 25/50 D, BPR35/60 BPR 35/60 D, BPR 50/55 D BPR 55/65 D, BPR 60/65 D

## **Reversible Hydraulic Plate**



Centrifugal force: 80 kN Working width: 800 mm

## **Hand-guided Single Drum Vibratory Rollers**



Centrifugal force: 10 kN Working width: 560 mm



Centrifugal force: 16 kN Working width: 710 mm

### **Single Direction Vibratory Plates**



### **Reversible Vibratory Plates**



Centinugal force: 25 Rn Working width: 400 mm



EPH 25,40 U centriugai iorce: 25 kiV Working width: 400 mm



Centribgar ibrce: 25 kiv Working width: 500 mm



centritugar förce: 25 km Working width: 500 mm



Centrifugai Torce: 35 кі Working width: 420 mm



BPR 55.455 D Centrifugal force: 55 kN Working width: 650 mm



Centrifugal force: 60 kN Working width: 650 mm



BFR 60/65 D Centrifugal force: 60 kN Working width: 650 mm



BPR 70 70 D Centrifugal force: 70 kN Working width: 700 mm



BPR 10CVBD D Centrifugal force: 100 kN Working width: 800 mm

### **Hand-guided Double Drum Vibratory Rollers**



Centrifugal force: 22 kN Working width: 650 mm



Centrifugal force: 40 kN Working width: 750 mm not available in US + CN + IN

### **Multipurpose Compactor**



Centrifugal force: 72/36 kN Working width: 610 mm / 850 mm



